

## **APPENDIX NIM (NETWORK INTERCONNECTION METHODS)**

## TABLE OF CONTENTS

1.	INTRODUCTION.....	3
2.	PHYSICAL ARCHITECTURE.....	3
3.	METHODS OF INTERCONNECTION.....	5
4.	RESPONSIBILITIES OF THE PARTIES.....	8
5.	JOINT FACILITY GROWTH PLANNING.....	9
6.	APPLICABILITY OF OTHER RATES, TERMS AND CONDITIONS ..	10

**APPENDIX NIM  
(NETWORK INTERCONNECTION METHODS)**

**1. INTRODUCTION**

- 1.1 This Appendix sets forth the terms and conditions that Network Interconnection Methods (NIM) are provided by TDS TELECOM and SPRINT. This Appendix describes the physical architecture for Interconnection of the Parties' facilities and equipment for the transmission and routing of Telephone Exchange Service traffic and Exchange Access traffic between the respective Customers of the Parties; provided, however, Interconnection may not be used solely for the purpose of originating a Party's own interexchange traffic.
- 1.2 Network Interconnection Methods (NIMs) include, but are not limited to, Leased Facilities Interconnection; Fiber Meet Interconnection; and other methods as mutually agreed to by the Parties.
  - 1.2.1 Trunking requirements associated with Interconnection are contained in Appendix ITR.
- 1.3 TDS TELECOM shall provide Interconnection for SPRINT's facilities and equipment for the transmission and routing of Telephone Exchange Service and Exchange Access, at a level of quality equal to that which TDS TELECOM provides itself, a subsidiary, an affiliate, or any other party to which TDS TELECOM provides Interconnection and on rates, terms and conditions that are just, reasonable and non-discriminatory.
- 1.4 The Parties shall effect an Interconnection that is efficient, fair and in a manner that is mutually agreeable to the Parties.

**2. PHYSICAL ARCHITECTURE**

- 2.1 TDS TELECOM's network is partly comprised of End Office switches that serve IntraLATA, InterLATA, Local, and EAS traffic. TDS TELECOM's network architecture in any given local exchange area and/or LATA can vary markedly from another local exchange area/LATA. Using one or more of the NIMs herein, the Parties will agree to a physical architecture plan for a specific Exchange Area. The physical architecture plan will be completed within sixty (60) days from SPRINT's written request for interconnection contingent upon the Parties' mutual agreement on the architecture. SPRINT and TDS TELECOM agree to Interconnect their networks through existing and/or new Interconnection facilities between SPRINT switch(es) and TDS TELECOM's End Office(s). The physical architecture plan will, at a minimum, include the location of SPRINT's switch(es) and TDS TELECOM End Office switch(es) to be interconnected, the facilities that will connect the two networks, the timelines for completion of all major tasks,

and which Party will provide (be financially responsible for) the Interconnection facilities. At the time of implementation in a given local exchange area the plan will be documented and signed by appropriate representatives of the Parties, indicating their mutual agreement to the physical architecture plan.

- 2.2 Points of Interconnection (POIs): A Point of Interconnection (POI) is a point in the network where the Parties deliver Local Traffic to each other, and also serves as a demarcation point between the facilities that each Party is responsible to provide. At least one POI must be established for each Exchange Area where TDS TELECOM operates as an ILEC and SPRINT has End Users in that same area, except where TDS provides host/remote configurations, pursuant to ITR section 4.2. In some cases, multiple POI(s) will be necessary to balance the facilities investment and provide the best technical implementation of Interconnection requirements to each End Office within a TDS TELECOM company's service area. Both Parties shall negotiate the architecture in each location that will seek to mutually minimize and equalize investment. The initial mutually agreed upon POI(s) is described in Attachment A of this Appendix.
- 2.3 The Parties agree to meet as often as necessary to negotiate the selection of new POIs. The overall goal of POI selection will be to achieve a balance in the provision of facilities that is fair to both Parties. Criteria to be used in determining POIs include existing facility capacity, location of existing POIs, traffic volumes, relative costs, future capacity needs, etc. Agreement to the location of POIs will be based on the network architecture existing at the time the POI(s) is/are negotiated. In the event either Party makes subsequent changes to its network architecture, including but not limited to trunking changes or adding new switches, then the Parties will negotiate new POIs if required. The mutually agreed to POIs will be documented and distributed to both Parties.
- 2.4 Each Party is responsible for the facilities to its side of the POI(s) and may utilize any method of Interconnection described in this Appendix. Each Party is responsible for the appropriate sizing, operation, and maintenance of the transport facility to the POI(s).
- 2.5 Either Party, must provide thirty (30) days written notice of any changes to the physical architecture plan.
- 2.6 Each Party is solely responsible for the facilities that carry OS/DA, 911 or mass calling for their respective End Users.
- 2.7 Technical Interfaces



- 2.7.1 The Interconnection facilities provided by each Party shall be formatted using B8ZS with Extended Superframe format framing.
- 2.7.2 Electrical handoffs at the POI(s) will be DS1, DS3 or STS-1 as mutually agreed to by the parties. When a DS3 or STS-1 handoff is agreed to by the Parties, each Party will provide all required multiplexing at their respective end.

### 3. METHODS OF INTERCONNECTION

#### 3.1 Leased Facility Interconnection ("LFI")

- 3.1.1 Where facilities exist, either Party may lease facilities from the other Party pursuant to applicable tariff. The rate for two-way facilities provided by TDS TELECOM and dedicated to traffic between SPRINT and TDS TELECOM will be reduced by a shared facility factor of forty percent (40%) to account for the estimated portion of the facility utilized to carry TDS TELECOM originated traffic.

#### 3.2 Fiber Meet Interconnection

- 3.2.1 Fiber Meet Interconnection between TDS TELECOM and SPRINT can occur at any mutually agreeable, economically and technically feasible point(s) between SPRINT's premises and a TDS TELECOM End Office.
- 3.2.2 Where the Parties interconnect their networks pursuant to a Fiber Meet, the Parties shall jointly engineer and operate this Interconnection as a Synchronous Optical NETWORK (SONET) ring or single point-to-point linear SONET system. Administrative control of the SONET system shall be mutually agreed upon by the Parties. Only Interconnection trunks or trunks used to provide ancillary services as described in Section 5 of Appendix ITR shall be provisioned over this facility.
- 3.2.3 Neither Party will be given the IP address or allowed to access the Data Communications Channel (DCC) of the other Party's Fiber Optic Terminal (FOT). The Fiber Meet will be designed so that each Party may, as far as is technically feasible, independently select the transmission, multiplexing, and fiber terminating equipment to be used on its side of the POI(s). The Parties will work cooperatively to achieve equipment and vendor compatibility of the FOT equipment. Requirements for such Interconnection specifications will be defined in joint engineering planning sessions between the Parties. The Parties may share the investment of the fiber as mutually agreed. The Parties will use good faith efforts to develop and agree on these facility arrangements within ninety (90) days of the determination by the Parties that such specifications shall

be implemented, and in any case, prior to the establishment of any Fiber Meet arrangements between them.

3.2.4 There are four basic Fiber Meet design options.

3.2.4.1 Design One: SPRINT's fiber cable (four, or some integral multiple thereof, fibers) and TDS TELECOM's fiber cable (four, or some integral multiple thereof, fibers) are connected at an economically and technically feasible point between the SPRINT and TDS TELECOM locations. This Interconnection point would be at a mutually agreeable location.

3.2.4.2 Design Two: SPRINT will provide fiber cable to the last entrance (or TDS TELECOM designated) manhole at the TDS TELECOM's End Office switch. TDS TELECOM shall make all necessary preparations to receive and to allow and enable SPRINT to deliver fiber optic facilities into that manhole. SPRINT will provide a sufficient length of Optical Fire Resistant (OFR) cable for TDS TELECOM to pull the fiber cable through the TDS TELECOM cable vault and terminate on the TDS TELECOM fiber distribution frame (FDF) in TDS TELECOM's office. SPRINT shall deliver and maintain such strands wholly at its own expense up to the POI. TDS TELECOM shall take the fiber from the manhole and terminate it inside TDS TELECOM's office on the FDF at TDS TELECOM's expense. In this case the POI shall be at the TDS TELECOM designated manhole location.

3.2.4.3 Design Three: TDS TELECOM will provide fiber cable to the last entrance (or SPRINT designated) manhole at the SPRINT location. SPRINT shall make all necessary preparations to receive and to allow and enable TDS TELECOM to deliver fiber optic facilities into that manhole. TDS TELECOM will provide a sufficient length of Optical Fire Resistant (OFR) cable for SPRINT to run the fiber cable from the manhole and terminate on the SPRINT fiber distribution frame (FDF) in SPRINT's location. TDS TELECOM shall deliver and maintain such strands wholly at its own expense up to the POI. SPRINT shall take the fiber from the manhole and terminate it inside SPRINT's office on the FDF at SPRINT's expense. In this case the POI shall be at the SPRINT designated manhole location.

3.2.4.4 Design Four: Both SPRINT and TDS TELECOM each provide two fibers between their locations. This design may only be considered where existing fibers are available and there is a mutual benefit to both Parties. TDS TELECOM will provide the fibers associated

with the "working" side of the system. SPRINT will provide the fibers associated with the "protection" side of the system. The Parties will work cooperatively to terminate each other's fiber in order to provision this joint SONET ring or point-to-point linear system. Both Parties will work cooperatively to determine the appropriate technical handoff for purposes of demarcation and fault isolation. The POI will be defined as being at the TDS TELECOM location.

- 3.2.5 The SPRINT location includes FOTs, multiplexing and fiber required to terminate the optical signal provided from TDS TELECOM. This location is SPRINT's responsibility to provision and maintain.
- 3.2.6 The TDS TELECOM location includes all TDS TELECOM FOTs, multiplexing and fiber required to terminate the optical signal provided from SPRINT. This location is TDS TELECOM's responsibility to provision and maintain.
- 3.2.7 TDS TELECOM and SPRINT shall, solely at their own expense, procure, install, and maintain the agreed-upon FOT equipment in each of their locations where the Parties established a Fiber Meet. Capacity shall be sufficient to provision and maintain all trunk groups prescribed by Appendix ITR for the purposes of Interconnection.
- 3.2.8 Each Party shall provide its own, unique source for the synchronized timing of its FOT equipment. At a minimum, each timing source must be Stratum-3 traceable and cannot be provided over DS0/DS1 facilities, via Line Timing; or via a Derived DS1 off of FOT equipment. Both Parties agree to establish separate and distinct timing sources that are not derived from the other, and meet the criteria identified above.
- 3.2.9 SPRINT and TDS TELECOM will mutually agree on the capacity of the FOT(s) to be utilized based on equivalent DS1s, DS3s or STS-1s. Each Party will also agree upon the optical frequency and wavelength necessary to implement the Interconnection. The Parties will develop and agree upon methods for the capacity planning and management for these facilities, terms and conditions for over provisioning facilities, and the necessary processes to implement facilities as indicated below. These methods will meet quality standards as mutually agreed to by SPRINT and TDS TELECOM.

### 3.3 Indirect Interconnection



3.3.1 The Parties agree that where traffic volumes do not warrant direct interconnection, traffic shall be exchanged by transiting such traffic through third party LEC tandems. Each Party shall be financially and operationally responsible for the entire cost of providing facilities from its network to the Point of Interconnection (POI) for the exchange of such traffic.

3.3.2 Where the traffic exchanged between SPRINT and a specific TDS TELECOM host or end office switch requires twenty-four (24) or more trunks or it is otherwise economically advantageous, the Parties shall implement direct trunks to a POI associated with the specific host or end office switch in accordance with Appendix ITR Section 4.

#### **4. RESPONSIBILITIES OF THE PARTIES**

4.1 If SPRINT determines to offer local exchange service within a TDS TELECOM area, SPRINT shall provide thirty (30) days written notice to TDS TELECOM of the need to establish Interconnection. Such request shall include (i) SPRINT's Switch address, type, and CLLI; (ii) SPRINT's requested Interconnection activation date; and (iii) a non-binding forecast of SPRINT's trunking and facilities requirements.

4.2 Upon receipt of SPRINT's notice to interconnect, the Parties shall schedule a meeting to negotiate and mutually agree on the network architecture (including trunking) to be documented as discussed above. The Interconnection activation date for an Interconnect shall be established based on then-existing work force and load, the scope and complexity of the requested Interconnection and other relevant factors.

4.3 If SPRINT deploys additional switches after the Effective Date or otherwise wishes to establish Interconnection with additional TDS TELECOM Central Offices, SPRINT shall provide written notice to TDS TELECOM to establish such Interconnection. The terms and conditions of this Agreement shall apply to such Interconnection. If TDS TELECOM deploys additional End Office switches in a local exchange after the effective date or otherwise wishes to establish Interconnection with additional SPRINT Central Offices in such local exchange, TDS TELECOM shall be entitled, upon written notice to SPRINT, to establish such Interconnection and the terms and conditions of this Agreement shall apply to such Interconnection.

4.4 SPRINT and TDS TELECOM shall work cooperatively to install and maintain a reliable network. SPRINT and TDS TELECOM shall exchange appropriate information (e.g., maintenance contact numbers, network information, information required to comply with law enforcement and other security agencies



of the federal and state government and such other information as the Parties shall mutually agree) to achieve this desired reliability.

- 4.5 SPRINT and TDS TELECOM will review engineering requirements as required and establish semi-annual forecasts for facilities utilization provided under this Appendix.
- 4.6 SPRINT and TDS TELECOM shall:
  - 4.6.1 Provide trained personnel with adequate and compatible test equipment to work with each other's technicians.
  - 4.6.2 Notify each other when there is any change affecting the service requested, including the due date.
  - 4.6.3 Recognize that a facility handoff point must be agreed to that establishes the demarcation for maintenance and provisioning responsibilities for each party on their side of the POI.

## 5. JOINT FACILITY GROWTH PLANNING

- 5.1 The initial fiber optic system deployed for each Interconnection shall be agreed to by the Parties. The following lists the criteria and processes needed to satisfy additional capacity requirements beyond the initial system.
- 5.2 Criteria:
  - 5.2.1 Investment is to be minimized.
  - 5.2.2 Facilities will be planned for in accordance with the trunk forecasts exchanged between the Parties as described in Appendix ITR and are to be deployed in accordance with the Processes described below.
- 5.3 Processes:
  - 5.3.1 In addition to the semi-annual forecast process, discussions to provide relief to existing facilities can be initiated by either party. Actual system augmentations will be initiated upon mutual agreement.
  - 5.3.2 Both Parties will perform a joint validation to ensure current Interconnection facilities and associated trunks have not been over-provisioned. If any facilities and/or associated trunks are over-provisioned, they will be turned down where appropriate. Trunk design blocking criteria described in Appendix ITR will be used in determining trunk group sizing requirements and forecasts.

- 5.3.3 If, based on the forecasted equivalent DS-1 growth, the existing fiber optic system is not projected to exhaust within one year, the Parties will suspend further relief planning on this Interconnection until a date one (1) year prior to the projected exhaust date. If growth patterns change during the suspension period, either Party may re-initiate the joint planning process.
- 5.3.4 If the placement of a minimum size system will not provide adequate augmentation capacity for the joint forecast over a two-year period and the forecast appears reasonable, the next larger system may be deployed. If the forecast does not justify a move to the next larger system, another appropriately sized system could be placed. This criterion assumes both Parties have adequate fibers for either scenario. If adequate fibers do not exist, both Parties would negotiate placement of additional fibers.
- 5.3.5 Both Parties will negotiate a project service date and corresponding work schedule to construct relief facilities prior to facilities exhaust.
- 5.3.6 The joint planning process/negotiations should be completed within two months of the initiation of such discussion.

## **6. APPLICABILITY OF OTHER RATES, TERMS AND CONDITIONS**

- 6.1 Every interconnection and service provided hereunder shall be subject to all rates, terms and conditions contained in this Agreement which are legitimately related to such interconnection or service.

TDS Telecom/ Sprint  
Points of Interconnection

The Parties agree initially to interconnect on an indirect basis pursuant to Section 3.3.1 of this Appendix. At such time as the traffic thresholds described in Section 3.3.2 are met or the Parties otherwise determine to implement direct interconnection, the mutually agreed upon Point(s) of Interconnection between Sprint and TDS Telecom for the exchange of traffic will be as described below.


Technical Point of Contact for:

Sprint: Brian Snyder 913-762-1859

TDS Telecom: Wade Soczka- Mgr. Network Implementation Support- 608-664-4847

Exchange(s)	POI- Description	POI- CLLI	Location	Vertical/ Horizontal Coordinates
Cleveland, WI Collins, WI Howards Grove, WI St. Nazianz, WI Valders, WI	Cleveland Host Office	CLEVWIXADS1	1140 W WASHINGTON AVE	V= 05606 H= 03651
Stockbridge, WI Sherwood, WI	Sherwood Host Office	SHWDWIXADSA	287 N MILITARY	V= 05594 H= 03748
Tisch Mills, WI	Tisch Mills End Office	TSMLWIXADS0	CTY TRK B	V=05519 H= 03676


By Sprint Communications, L.P.

 1/26/06  
Signature Date

Gary Lindsey  
Printed Name

Director – Access Solutions  
Position/Title

By TDS Telecommunications Corporation,  
agent

 2/2/06  
Signature Date

Louis D. Reilly, III  
Printed Name

Director - Carrier Relations  
Position/Title